

产品型号 (Product Model) : JB1500-716M716M-4.2M
产品物料 (Product Materials) : 13.01.CA19208

产品特点(Product Features):

- 1.良好的稳定性
- 2.高功率, 低损耗
- 3.可按客户要求设计和生产



电气性能 (Electrical Properties) :

技术指标 (Technical Indicators)	参数 (Parameter)
频率 (Frequency Range)	DC-1GHz
阻抗 (Impedance)	50Ω
驻波比 (VSWR)	≤1.1@1GHz
插入损耗 (Insertion loss)	≤0.65dB@1GHz
绝缘电阻 (Insulation Resistance)	≥5000MΩ
介质耐压 (Dielectric Strength)	≥3500V

机械性能 (Mechanical Properties) :

名称 (Name)	材质 (Texture of)
电缆-中心导体 (Cable center conductor)	镀银铜
电缆-绝缘体 (Cable Insulator)	LD-PTFE
电缆-外导体 (Cable Outer Conductor)	镀银铜带
电缆-中屏蔽 (Cable Inner Shielding)	PICA
电缆-外屏蔽 (Cable Outer shielding)	镀银铜丝
电缆-外护套 (Cable Jacket)	FEP(Blue)
使用温度 (Operating Temperature)	-55~125°C
连接器-绝缘体 (Connector Insulator)	PTFE
连接器-外导体 (Connector Outer contact)	黄铜镀三元合金
连接器-中心导体 (Connector Center contact)	黄铜镀银

产品外观尺寸(Product Appearance Size) :

